



MGB / MGC

There are some things you can always depend on...

Gas Fired Hot Water Boiler

Up to 83.9% AFUE

Energy saving features include the electronic ignition system and motorized vent damper to reduce your heating costs.

Dependable Cast Iron Heat Exchanger with Cast Iron Push Nipples

Cast iron sections are sealed into a heat exchanger by push nipple connections. This is a superior method of construction compared to competitor's use of steel push nipples or neoprene gasket connections.

Choice of Two Operating Controls

Honeywell or HydroLevel 3250

- Standard Honeywell control, with digital display and diagnostics, monitors water temperature and delays burner from starting until the residual heat energy within the boiler is consumed.
- Optional HydroLevel control, with digital display and diagnostics, adjusts the water temperature based on your heating system demand which further reduces your heating costs. It also features a built-in low water cut-off (LWCO) to protect the boiler from potentially dangerous low water conditions.

Integral Draft Diverter

- Features factory installed integrated draft hood diverter, which reduces the risk of improper draft hood installation and unsafe CO levels.
- Low profile reduces installation height by up to 30" as compared to models with external draft diverter hood.









Limited Lifetime Heat Exchanger Warranty

Built by American craftsmen since 1928

**Optional
HydroLevel
Boiler Control!**



Utica MGB Series II & MGC Series Gas Fired Hot Water Boiler

Dimensional Diagram	Model	Input Rate (MBH) ⁽¹⁾	Heating Capacity (MBH) ⁽¹⁾	Net AHRI Rating, Water (MBH) ⁽²⁾	Expansion Tank ⁽³⁾	No. of Burners	AFUE %																																																																		
 <p>MGB Front</p>	MGB-50J	50	42	37	15	1	83.5%																																																																		
	MGB-75J	75	63	55	15	2	83.1%																																																																		
	MGB-100J	100	83	72	30	2	83.0%																																																																		
	MGB-125J	125	104	90	30	3	82.0%																																																																		
	MGB-150J	150	124	108	30	3	83.0%																																																																		
	MGB-170J	170	139	121	30	4	82.0%																																																																		
	MGB-200J	200	165	143	30	4	82.0%																																																																		
	MGC-8D/DP*	262.5/245	220/206	191/179	60	7	83.9%																																																																		
	MGC-9D/DP*	299/280	251/235	218/204	60	8	83.7%																																																																		
<p>*D=Natural Gas, DP=LP Gas The MGC has distinct input rates for Natural and LP gas versions. 8D/9D rates shown are for Natural gas. 8DP/9DP rates are for LP gas. (1) Input rating for sea level to 2,000 ft. (610m) above sea level. United States, over 2000 ft (610m) above sea level. Reduce input rate 4% for every 1000 ft (304m) above sea level. (2) Net AHRI Water Ratings shown based on piping and pickup allowance of 1.15. Consult manufacturer before selecting boiler for installations having unusual piping and pickup requirements, such as intermittent system operation, extensive piping systems, etc. For forced hot water systems where boiler and all piping within area to be heated, boiler may be selected on basis of its heating capacity. (3) Recommended tank sizes for non-ferrous baseboard or radiant panel systems. Increase size for cast iron baseboard and radiation.</p>																																																																									
<p>General Information (See Installation, Operation and Maintenance Manual for complete instructions)</p>																																																																									
 <p>MGB Side</p>	<p>Clearances (4) Required distances measured from boiler.</p>		<p>Combustible Materials (Required) ⁽⁴⁾</p> <table border="1"> <thead> <tr> <th></th> <th>MGB</th> <th>MGC</th> </tr> </thead> <tbody> <tr> <td>Top</td> <td>18" (457 mm)</td> <td>6" (152 mm)</td> </tr> <tr> <td>Control Side</td> <td>9" (229 mm)</td> <td>7" (178 mm)</td> </tr> <tr> <td>Other Side</td> <td>3" (76mm)</td> <td>6" (152 mm)</td> </tr> <tr> <td>Front</td> <td>Alcove*</td> <td>18" (457 mm)</td> </tr> <tr> <td>Rear</td> <td>4" (102 mm)</td> <td>6" (152 mm)</td> </tr> <tr> <td>Flue Connector</td> <td>6" (152 mm)</td> <td>6" (152 mm)</td> </tr> </tbody> </table>						MGB	MGC	Top	18" (457 mm)	6" (152 mm)	Control Side	9" (229 mm)	7" (178 mm)	Other Side	3" (76mm)	6" (152 mm)	Front	Alcove*	18" (457 mm)	Rear	4" (102 mm)	6" (152 mm)	Flue Connector	6" (152 mm)	6" (152 mm)																																													
		MGB	MGC																																																																						
	Top	18" (457 mm)	6" (152 mm)																																																																						
	Control Side	9" (229 mm)	7" (178 mm)																																																																						
	Other Side	3" (76mm)	6" (152 mm)																																																																						
	Front	Alcove*	18" (457 mm)																																																																						
	Rear	4" (102 mm)	6" (152 mm)																																																																						
Flue Connector	6" (152 mm)	6" (152 mm)																																																																							
<p>*Definition of Alcove is three sided space with no wall in front of boiler. ANSI standard for alcove is 18 inches from appliance to leading edge of side walls as shown in IOM.</p>																																																																									
<p>Connections (All Models) Return/Supply Water 1-1/4", Gas In 1/2" NPT</p>																																																																									
<p>Electrical 120 Volts AC, 60 hertz, 1 phase, Less than 12 amps (15 amp circuit recommended)</p>																																																																									
<p>Water Content 50 - 2.4 Gallons, 75/100 - 4.0 Gallons, 125/150 - 5.6 Gallons, 170/200 - 7.2 Gallons, 262.5 - 12.7 Gallons, 299 - 14.4 Gallons</p>																																																																									
 <p>MGC Front</p>	<p>Dimensions/Weights</p>		<table border="1"> <thead> <tr> <th>Model</th> <th>A</th> <th>B</th> <th>C</th> <th>D</th> <th>Weight</th> </tr> </thead> <tbody> <tr> <td>MGB-50J</td> <td>11-1/8"</td> <td>4"</td> <td>30-3/4"</td> <td>36-1/4"</td> <td>205 lbs.</td> </tr> <tr> <td>MGB-75J</td> <td>15"</td> <td>5"</td> <td>30-3/4"</td> <td>37-3/4"</td> <td>253 lbs.</td> </tr> <tr> <td>MGB-100J</td> <td>15"</td> <td>6"</td> <td>30-3/4"</td> <td>37-1/4"</td> <td>253 lbs.</td> </tr> <tr> <td>MGB-125J</td> <td>18-7/8"</td> <td>6"</td> <td>30-3/4"</td> <td>37-1/4"</td> <td>315 lbs.</td> </tr> <tr> <td>MGB-150J</td> <td>18-7/8"</td> <td>7"</td> <td>30-3/4"</td> <td>37-3/4"</td> <td>315 lbs.</td> </tr> <tr> <td>MGB-170J</td> <td>22-3/4"</td> <td>7"</td> <td>30-3/4"</td> <td>38-3/4"</td> <td>377 lbs.</td> </tr> <tr> <td>MGB-200J</td> <td>22-3/4"</td> <td>8"</td> <td>30-3/4"</td> <td>38-3/4"</td> <td>377 lbs.</td> </tr> <tr> <th>Model</th> <th>A</th> <th>C</th> <th>D</th> <th>E</th> <th>Weight</th> </tr> <tr> <td>MGC-8D/DP</td> <td>27-1/2"</td> <td>7"</td> <td>36-3/8"</td> <td>41-7/8"</td> <td>552 lbs.</td> </tr> <tr> <td>MGC-9D/DP</td> <td>30-3/4"</td> <td>7"</td> <td>36-3/8"</td> <td>41-7/8"</td> <td>616 lbs.</td> </tr> </tbody> </table>					Model	A	B	C	D	Weight	MGB-50J	11-1/8"	4"	30-3/4"	36-1/4"	205 lbs.	MGB-75J	15"	5"	30-3/4"	37-3/4"	253 lbs.	MGB-100J	15"	6"	30-3/4"	37-1/4"	253 lbs.	MGB-125J	18-7/8"	6"	30-3/4"	37-1/4"	315 lbs.	MGB-150J	18-7/8"	7"	30-3/4"	37-3/4"	315 lbs.	MGB-170J	22-3/4"	7"	30-3/4"	38-3/4"	377 lbs.	MGB-200J	22-3/4"	8"	30-3/4"	38-3/4"	377 lbs.	Model	A	C	D	E	Weight	MGC-8D/DP	27-1/2"	7"	36-3/8"	41-7/8"	552 lbs.	MGC-9D/DP	30-3/4"	7"	36-3/8"	41-7/8"	616 lbs.
	Model	A	B	C	D	Weight																																																																			
	MGB-50J	11-1/8"	4"	30-3/4"	36-1/4"	205 lbs.																																																																			
	MGB-75J	15"	5"	30-3/4"	37-3/4"	253 lbs.																																																																			
	MGB-100J	15"	6"	30-3/4"	37-1/4"	253 lbs.																																																																			
	MGB-125J	18-7/8"	6"	30-3/4"	37-1/4"	315 lbs.																																																																			
	MGB-150J	18-7/8"	7"	30-3/4"	37-3/4"	315 lbs.																																																																			
	MGB-170J	22-3/4"	7"	30-3/4"	38-3/4"	377 lbs.																																																																			
	MGB-200J	22-3/4"	8"	30-3/4"	38-3/4"	377 lbs.																																																																			
Model	A	C	D	E	Weight																																																																				
MGC-8D/DP	27-1/2"	7"	36-3/8"	41-7/8"	552 lbs.																																																																				
MGC-9D/DP	30-3/4"	7"	36-3/8"	41-7/8"	616 lbs.																																																																				
<p>Standard Equipment</p> <p>Boiler Control Module: Choice of Honeywell Control (High Limit/Electronic Ignition Control) with plastic cover and display window; or Hydrolevel Fuel Smart Control (High Limit/LWCO) User Display Interface: Digital Temperature Display Heat Exchanger: Cast Iron Sections with Cast Iron Push Nipples. Combustion: Stainless Steel Main Gas Burners (MGB)/Titanium Composite Burners (MGC), Combination 24 Volt Gas Control (Includes: Automatic Gas Valve, Gas Pressure Regulator, Automatic Pilot, Safety Shutoff, Pilot Flow Adjustment, Pilot Filter), Intermittent Pilot Control, Continuous Retry, Combination Pilot Burner/Electrode/Flame Sensor. Safety: Spill Switch and Roll-Out Switch for safety, Automatic Vent Damper. Other: Insulated Boiler Jacket, Integral Draft Diverter, Combination Temperature/Pressure Gauge, 3/4" Drain Valve, 30lb. ASME Relief Valve. MAWP Maximum Allowable Working Pressure 100 psi (MGB) & 50 psi (MGC).</p>																																																																									
<p>Options Available in both natural gas or propane models. Central Heating Pump (Taco, Grundfos, B&G or Less Pump), LP Conversion Kit, Combustible Floor Plate, Fill-Trol.</p>																																																																									
 <p>MGC Side</p>	<p>Certifications</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <small>C.S.A. Certified For Natural Gas Or Propane</small> </div> <div style="text-align: center;">  <small>C US</small> </div> <div style="text-align: center;">  <small>Tested for 100 psi (MGB) / 50 psi (MGC) ASME Working Pressure</small> </div> <div style="text-align: center;">  <small>www.ahridirectory.org</small> </div> </div>																																																																								

All ratings and specifications subject to change.

PN 240009709 Rev. 1/17



ECR International: 2201 Dwyer Ave., Utica, NY 13501 Tel: 315-797-1310
 or 800-325-5479 Fax: 315-724-9319 www.ecrinternational.com

In Canada: Contact ECR Master Representative: Morden National Sales and Marketing Inc. Tel: 519-627-0791 Fax: 866-835-6667 www.mordennational.com

