



## Model: AWA2460ZXT

### Product Description

**Type:** Reciprocating  
**Application:** LBP - Low Back Pressure  
**Refrigerant:** R-404A  
**Voltage/Frequency:** 200-230V 3~ 60Hz 200-220V 3~  
 50Hz  
**Version:** N/A

### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power W	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W		Btu/Wh	kcal/Wh	W/W					
ARI	230V 3~ 60HZ	6000	1512	1758	1630	3.68	.93	1.08	-23°C (-10°F)	49°C (120°F)	35°C (95°F)	4.4°C (40°F)	49°C (120°F)

#### General

**Evaporating Temp. Range:** -40°C to -12.2°C (-40°F to 10°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

#### Mechanical

**Weight:** 67  
**Weight Unit of Measure:** LB  
**Displacement (cc):** 53.49  
**Oil Type:** Polyolester  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 1141

#### Electrical

**Voltage Range (50 Hz):** 180-242  
**Voltage Range (60 Hz):** 180-254  
**Locked Rotor Amps (LRA):** 63.4  
**Rated Load Amps (RLA 50 Hz):** 0  
**Rated Load Amps (RLA 60 Hz):** 5.6  
**Max. Continuous Current (MCC in Amps):** 13  
**Motor Resistance (Ohm) - Main:** 1.28  
**Motor Resistance (Ohm) - Start:** N/A  
**Motor Type:** 3PH  
**Overload Type:** N/A  
**Relay Type:** N/A

#### Agency Approval

cURus Recognized